

# SO-QSFP-SR4

QSFP+, 40G Ethernet SR4, MM 850nm, 150m@OM4, 1.9dB, MPO

## OVERVIEW

The SO-QSFP-SR4 is a 40GBASE-SR4 compliant QSFP+ (Quad Small Form-factor Pluggable Plus) transceiver for 40 Gbps applications where the transport is made using four channels at 10 Gbps. It is intended for use in intra-connect applications in data centers between switches, routers, storage equipment etc. The transceiver can also be used for 10GbE-LAN interconnect applications, providing a higher density as compared to four individual 10G connections using e.g. SFP+ transceivers.

The SO-QSFP-SR4 provides transport over an MPO/MTP 12 or 8 ribbon fiber cable up to 150 m when using an OM4-grade MultiMode (MM) fiber.

## TECHNICAL DATA

Parameter	Value
Technology	Grey QSFP+
Transmission media	MM (1x MPO8/MPO12)
Typical reach	150m (OM4), 100m (OM3)
Nominal wavelength	4x 850nm
Interface standards	40GBASE-SR4
Bit rate support	41.25Gbps <sup>1)</sup> 4x 10.3125Gbps <sup>2)</sup>
Protocol support	40GbE / 4x 10GbE-LAN
Power budget	0 – 1.9dB
Power consumption	< 1.5W
Operating temperature	0°C to +70°C
Storage temperature	-40°C to +85°C

<sup>1)</sup> Aggregated line rate

<sup>2)</sup> Per lane

<sup>3)</sup> Average power

<sup>4)</sup> At BER less than  $10^{-12}$ , with a  $2^{31}-1$  PRBS

Parameter	Value
<b>Transmitter data:</b>	
Output power, per lane	Min: -7.6dBm <sup>3)</sup> Max: +2.4dBm <sup>3)</sup>
Transmit wavelength	840 – 860nm
<b>Receiver data:</b>	
Minimum input power	-9.5dBm <sup>2) 3) 4)</sup>
Overload (max power)	+2.4dBm <sup>2) 3) 4)</sup>
Wavelength range	840 – 860nm
LOS Assert	Min -30dBm
LOS De-Assert	Max -7.5dBm
LOS Hysteresis	Min 0.5dB
DDM	Yes
MSA compliance	QSFP+ MSA, SFF-8436

### Safety/regulatory compliance:

TUV/UL/FDA (contact Smartoptics for latest certification information)

RoHS compliance

MPO (Multi-fiber Push On) is an optical connector for ribbon cables with four to twenty-four fibers. MTP is a specific brand of an MPO connector.

## ORDERING INFORMATION

Ordering number	Description
SO-QSFP-SR4	QSFP+, 40G Ethernet SR4, MM 850nm, 150m@OM4, 1.9dB, MPO

## GENERAL DEFINITIONS

Technology:	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable (DAC). Electrical or optical cable with attached connectors.
Transmission Media:	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach:	Nominal distance performance based on dispersion and power budget properties, i.e. w/o dispersion compensation and optical amplification.
Bit rate range:	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols:	Protocols within supported bit rate range.
Nominal wavelength:	Typical wavelength from transmitter.
Interface standards:	Referenced interface standards e.g. IEEE 802.3 standard for 10GbE services.
Power budget:	Min and max power budget between Transmitter and Receiver.
Dispersion tolerance/penalty:	Maximum amount of tolerated dispersion and required reduction of power budget to maintain stipulated Bit Error Rate (BER) and at a given bit rate.
Temperature range:	Max operating case temperature range. Commercial temperature range (C-temp): 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption:	Worst case power consumption. Will vary over temperature.
Transmitter Output power:	Average output power. Provided in min and max values.
Receiver minimum input power:	Minimum average input power at specified BER, normally 1E <sup>-12</sup> .
Receiver max input power:	Maximum average input power giving a BER, normally 1E <sup>-12</sup> .
DDM:	Digital Diagnostic Monitoring functionality as defined in SFF-8472 MSA.

Smartoptics makes no warranties or representations, expressed or implied, of any kind relative to the information or any portion thereof contained in this document or its adaptation or use, and assumes no responsibility or liability of any kind, including, but not limited to, indirect, special, consequential or incidental damages, for any errors or inaccuracies contained in the information or arising from the adaptation or use of the information or any portion thereof. The information in this document is subject to change without notice.