

SO-SFP-10GE-BX20D-2733/-3327

SFP+, BiDi, 10G Multirate, 1270/1330nm, DDM, 12dB, 20km

OVERVIEW

The SO-SFP-10GE-BX20D is a bi-directional transceiver solution operating directly on a single-fiber without the need for a separate optical filter. This is achieved by having two transceivers that inject different wavelengths into the same single-fiber. The solution thus consists of two transceivers; SO-SFP-10GE-BX20D-2733 and SO-SFP-10GE-BX20D-3327, operating at 1270nm and 1330nm respectively. Using a single-fiber solution provides a cost-efficient solution for interconnect and it simplifies the patching since no separate transmit/receive direction has to be taken into account.

The distance performance of the transceiver pair exceeds the IEEE 802.3ae LR-standard (10km), providing a bridgeable distance of up to 20km for 10GbE-LAN and 10GbE-WAN services.

The transceiver solution is available in two temperature range options, one being the Industrial temperature range (I-temp) of -40°C to +85°C (-40°F to +185°F).

This transceiver provides digital diagnostic functions via a 2-wire serial interface as defined by the SFF-8472 specification.

TECHNICAL DATA

Technology	BiDi SFP+
Transmission media	SM (1x LC)
Typical reach	20 km
Nominal wavelength	1270 nm ¹⁾ & 1330 nm ²⁾
Interface standards	10GBASE-LR 10GBASE-LW
Bit rate range	0.6 - 11.3 Gbps
Protocols	Eth: 10GbE-LAN 10GbE-WAN GbE
	OTN: OTU2 OTU2e OTU1
	SDH/SONET: STM-64/OC-192 STM-16/OC-48 STM-4/OC-12
	FC: 10G FC 8G FC 4G FC 1G FC
	CPRI: Opt 1 (0.6144 Gbps) Opt 2 (1.2288 Gbps) Opt 3 (2.4576 Gbps) Opt 4 (3.0720 Gbps) Opt 5 (4.9152 Gbps) Opt 6 (6.1440 Gbps) Opt 7 (9.8304 Gbps) Opt 7A (8.11008 Gbps) Opt 8 (10.1376 Gbps)
	OBSAI: 1x (0.768 Gbps) 2x (1.536 Gbps) 4x (3.0720 Gbps) 8x (6.1440 Gbps)
Power budget	2.5 - 12.0 dB
Temperature range	0°C to +70°C -40°C to +85°C (-I)
Power consumption	< 1.5W

Transmitter data	Output power:	Min: -2.0 dBm Max: +3.0 dBm
	Tx wavelength:	1260 - 1280 nm ¹⁾ 1320 - 1340 nm ²⁾
Receiver data	Minimum input power:	-14.0 dBm ³⁾
	Overload (max power):	+0.5 dBm
	Wavelength range:	1320 - 1340 nm ¹⁾ 1260 - 1280 nm ²⁾
DDM		Yes
MSA compliance		SFF-8431 SFF 8472

¹⁾ SO-SFP-10GE-BX20D-2733

²⁾ SO-SFP-10GE-BX20D-3327

³⁾ @ 10.3Gbps

Regulatory compliance

EMC CE	EN 55022:2010 EN 55024:2010
UL/Safety	UL 60950-1
FCC	47 CFR PART 15 OCT, 2013
RoHS	RoHS 6
TUV	EN 60950-1:2006+A11+A1+A12+A2 EN 60825-1:2014 EN 60825-2:2004+A1+A2

Storage temp.	-40°C to +85°C
----------------------	----------------

Note! See "Definitions" below.

Note: IEEE 802.3ae 10GBASE-LR/LW is defined only at 1310 nm. The standard is referred to from bridgeable distance perspective.

ORDERING INFORMATION

Part number	Description
SO-SFP-10GE-BX20D-2733	SFP+, BiDi, 10G Multirate, TX/RX=1270/1330nm, SM, DDM, 12dB, 20km
SO-SFP-10GE-BX20D-3327	SFP+, BiDi, 10G Multirate, TX/RX=1330/1270nm, SM, DDM, 12dB, 20km
SO-SFP-10GE-BX20D-2733-I	SFP+, BiDi, 10G Multirate, TX/RX=1270/1330nm, SM, DDM, 12dB, 20km, I-temp
SO-SFP-10GE-BX20D-3327-I	SFP+, BiDi, 10G Multirate, TX/RX=1330/1270nm, SM, DDM, 12dB, 20km, I-temp

DEFINITIONS

Technology:	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber.
Transmission Media:	DAC: Direct Attach Cable. Electrical or optical cable with attached connectors. Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach:	Nominal distance performance based on dispersion and power budget properties, i.e. w/o dispersion compensation and optical amplification.
Bit rate range:	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols:	Protocols within supported bit rate range.
Nominal wavelength:	Typical wavelength from transmitter.
Interface standards:	Referenced interface standards e.g. IEEE 802.3 standard for 10GbE services.
Power budget:	Min and max power budget between Transmitter and Receiver. Excluding any dispersion penalty.
Dispersion tolerance/penalty:	Maximum amount of tolerated dispersion and required reduction of power budget to maintain BER better than $1E^{-12}$. Defined at a specific bit rate.
Temperature range:	Max operating case temperature range. Standard temperature range: Typically 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): Typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption:	Worst case power consumption.
Transmitter Output power:	Average output power. Provided in min and max values.
Receiver minimum input power:	Minimum average input power at specified BER, normally $1E^{-12}$.
Receiver max input power:	Maximum average input power at specified BER, normally $1E^{-12}$.
DDM:	Digital Diagnostic Monitoring functionality as defined in SFF-8472 MSA.