

SO-SFP-10GE-ZR & -ZR-I

SFP+, 10G Multirate, 1550nm, SM, DDM, 23dB, 80km

OVERVIEW

The SO-SFP-10GE-ZR is a versatile 1550nm transceiver for SingleMode fiber supporting a wide range of traffic formats. The optical performance is in accordance with the industry ZR/ZW-standard, providing a bridgeable distance of up to 80km for 10GbE-LAN (10GBASE-ZR) and 10GbE-WAN (10GBASE-ZW) services.

This transceiver provides digital diagnostic functions via a 2-wire serial interface as defined by the SFF-8472 specification.

The transceiver is available in two temperature range options, one being the Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F).

TECHNICAL DATA

Technology	Grey SFP+
Transmission media	SM (2x LC)
Typical reach	80 km
Nominal wavelength	1550 nm
Interface standards	10GBASE-ZR 10GBASE-ZW
Bit rate range	0.6 - 11.3 Gbps
Protocols	Eth: 10GbE-LAN 10GbE-WAN GbE
	OTN: OTU2e OTU2 OTU1
	SDH/SONET: STM-64/OC-192 STM-16/OC-48 STM-4/OC-12
	FC: 10G FC 8G FC 4G FC 1G FC
	CPRI: Opt 1 (0.6144 Gbps) Opt 2 (1.2288 Gbps) Opt 3 (2.4576 Gbps) Opt 4 (3.0720 Gbps) Opt 5 (4.9152 Gbps) Opt 6 (6.1440 Gbps) Opt 7 (9.8304 Gbps) Opt 7A (8.11008 Gbps) Opt 8 (10.1376 Gbps)
	OBSAI: 1x (0.768 Gbps) 2x (1.536 Gbps) 4x (3.0720 Gbps) 8x (6.1440 Gbps)
Power budget	13.0 – 23.0 dB
Dispersion tolerance	1600 ps/nm ¹⁾
Dispersion penalty	3.0 dB ¹⁾
Temperature range	0°C to +70°C (ZR) -40°C to +85°C (ZR-I)
Power consumption	< 1.5W

Transmitter data	Output power:	Min: 0.0 dBm Max: +5.0 dBm
	Tx wavelength:	Min: 1528 nm Max: 1565 nm
Receiver data	Minimum input power:	-23.0 dBm ¹⁾
	Overload (max power):	-8.0 dBm
	Wavelength range:	1260 - 1600 nm
DDM		Yes
MSA compliance		SFF-8431 SFF-8432 SFF-8472

¹⁾ @ 10.3Gbps

Regulatory compliance

EMC CE	EN 55022:2010 EN 55024:2010
UL/Safety	UL 60950-1
FCC	47 CFR PART 15 OCT, 2013
RoHS	RoHS 6
TUV	EN 60950-1:2006+A11+A1+A12+A2 EN 60825-1:2014 EN 60825-2:2004+A1+A2

Storage temp.	-40°C to +85°C
----------------------	----------------

Note! See "Definitions" below.

ORDERING INFORMATION

Part number	Description
SO-SFP-10GE-ZR	SFP+, 10G Multirate, 1550nm, SM, DDM, 23dB, 80km
SO-SFP-10GE-ZR-I	SFP+, 10G Multirate, 1550nm, SM, DDM, 23dB, 80km, I-temp

DEFINITIONS

Technology:	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable (DAC). Electrical or optical cable with attached connectors.
Transmission Media:	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach:	Nominal distance performance based on dispersion and power budget properties, i.e. w/o dispersion compensation and optical amplification.
Bit rate range:	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols:	Protocols within supported bit rate range.
Nominal wavelength:	Typical wavelength from transmitter.
Interface standards:	Referenced interface standards e.g. IEEE 802.3 standard for 10GbE services.
Power budget:	Min and max power budget between Transmitter and Receiver. Excluding any dispersion penalty.
Dispersion tolerance/penalty:	Maximum amount of tolerated dispersion and required reduction of power budget to maintain BER better than $1E^{-12}$. Defined at a specific bit rate.
Temperature range:	Max operating case temperature range. Standard temperature range: typically 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption:	Worst case power consumption.
Transmitter Output power:	Average output power. Provided in min and max values.
Receiver minimum input power:	Minimum average input power at specified BER, normally $1E^{-12}$.
Receiver max input power:	Maximum average input power giving a BER, normally $1E^{-12}$.
DDM:	Digital Diagnostic Monitoring functionality as defined in SFF-8472 MSA.