

SO-SFP-MR80D-DXXXX

SFP, 100Mbps-2.7Gbps, DWDM 100GHz, DDM, 29dB, 80km, D9210-D9600 (40ch)

OVERVIEW

The SO-SFP-MR80D-Dxxxx is a DWDM transceiver covering a wide range of services up to 2.67Gbps, such as the SDH/SONET range STM-1/OC-3 to STM-16/OC-48 as well as 1Gbps Ethernet (GbE) services etc. The optical performance provides a bridgeable distance of up to 80 km without dispersion compensation. The transceiver is provided in 40 channel versions at the 100GHz DWDM grid as specified in the ITU-T 694.1 standard.

The transceiver provides digital diagnostic functions via a 2-wire serial interface as defined by the SFF-8472 specification. The transceiver module is compliant to RoHS-6/6.

TECHNICAL DATA

Technology	DWDM 100GHz SFP	
Transmission media	SM (2x LC)	
Typical reach	80 km	
Nominal wavelength	192.10 - 196.00 THz (40ch)	
Bit rate range	100 Mbps – 2.67 Gbps	
Protocols	Eth:	FE GbE
	SDH/SONET:	STM-1/OC-3 STM-4/OC-12 STM-16/OC-48
	OTN:	OTU1
	FC:	1G FC 2G FC
	CPRI:	Opt 1 (0.6144 Gbps) Opt 2 (1.2288 Gbps) Opt 3 (2.4576 Gbps)
	OBSAI:	0.768 Gbps 1.536 Gbps
Power budget	14.0 – 29.0 dB ¹⁾	
Dispersion tolerance	2080 ps/nm	
Temperature range	0°C to +70°C	
Power consumption	< 1.4W	

Transmitter data	Output power:	Min: 0.0 dBm Max: +5.0 dBm
	Tx wavelength:	192.10 - 196.00 THz in 100GHz steps (G.694.1)
Receiver data	Minimum input power:	-29.0 dBm ¹⁾
	Max input power:	-9.0 dBm
	Wavelength range:	1528 - 1620 nm
DDM	Yes	
MSA compliance	SFP MSA SFF-8472	

¹⁾ @ 2.488 Gbps & BER 1E-12

Regulatory compliance	
EMC CE	EN 55022:2010 EN 55024:2010
UL/Safety	UL 60950-1
FCC	47 CFR PART 15 OCT, 2013
RoHS	RoHS 6
TUV	EN 60950-1:2006+A11+A1+A12+A2 EN 60825-1:2014 EN 60825-2:2004+A1+A2

Storage temp.	-40°C to +85°C
----------------------	----------------

Note! See "Definitions" below.

ORDERING INFORMATION

Part number	Freq. THz	λ nm	Part number	Freq. THz	λ nm
SO-SFP-MR80D-D9210	192.10	1560.61	SO-SFP-MR80D-D9410	194.10	1544.53
SO-SFP-MR80D-D9220	192.20	1559.79	SO-SFP-MR80D-D9420	194.20	1543.73
SO-SFP-MR80D-D9230	192.30	1558.98	SO-SFP-MR80D-D9430	194.30	1542.94
SO-SFP-MR80D-D9240	192.40	1558.17	SO-SFP-MR80D-D9440	194.40	1542.14
SO-SFP-MR80D-D9250	192.50	1557.36	SO-SFP-MR80D-D9450	194.50	1541.35
SO-SFP-MR80D-D9260	192.60	1556.55	SO-SFP-MR80D-D9460	194.60	1540.56
SO-SFP-MR80D-D9270	192.70	1555.75	SO-SFP-MR80D-D9470	194.70	1539.77
SO-SFP-MR80D-D9280	192.80	1554.94	SO-SFP-MR80D-D9480	194.80	1538.98
SO-SFP-MR80D-D9290	192.90	1554.13	SO-SFP-MR80D-D9490	194.90	1538.19
SO-SFP-MR80D-D9300	193.00	1553.33	SO-SFP-MR80D-D9500	195.00	1537.40
SO-SFP-MR80D-D9310	193.10	1552.52	SO-SFP-MR80D-D9510	195.10	1536.61
SO-SFP-MR80D-D9320	193.20	1551.72	SO-SFP-MR80D-D9520	195.20	1535.82
SO-SFP-MR80D-D9330	193.30	1550.92	SO-SFP-MR80D-D9530	195.30	1535.04
SO-SFP-MR80D-D9340	193.40	1550.12	SO-SFP-MR80D-D9540	195.40	1534.25
SO-SFP-MR80D-D9350	193.50	1549.32	SO-SFP-MR80D-D9550	195.50	1533.47
SO-SFP-MR80D-D9360	193.60	1548.51	SO-SFP-MR80D-D9560	195.60	1532.68
SO-SFP-MR80D-D9370	193.70	1547.72	SO-SFP-MR80D-D9570	195.70	1531.90
SO-SFP-MR80D-D9380	193.80	1546.92	SO-SFP-MR80D-D9580	195.80	1531.12
SO-SFP-MR80D-D9390	193.90	1546.12	SO-SFP-MR80D-D9590	195.90	1530.33
SO-SFP-MR80D-D9400	194.00	1545.32	SO-SFP-MR80D-D9600	196.00	1529.55

DEFINITIONS

Technology:	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable. Electrical or optical cable with attached connectors.
Transmission Media:	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach:	Nominal distance performance based on dispersion and power budget properties, i.e. w/o dispersion compensation and optical amplification.
Bit rate range:	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols:	Protocols within supported bit rate range.
Nominal wavelength:	Typical wavelength from transmitter.
Interface standards:	Referenced interface standards e.g. IEEE 802.3 standard for 10GbE services.
Power budget:	Min and max power budget between Transmitter and Receiver. Excluding any dispersion penalty.
Dispersion tolerance/penalty:	Maximum amount of tolerated dispersion and required reduction of power budget to maintain BER better than $1E^{-12}$. Defined at a specific bit rate.
Temperature range:	Max operating case temperature range. Standard temperature range: Typically 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): Typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption:	Worst case power consumption.
Transmitter Output power:	Average output power. Provided in min and max values.
Receiver minimum input power:	Minimum average input power at specified BER, normally $1E^{-12}$.
Receiver max input power:	Maximum average input power at specified BER, normally $1E^{-12}$.
DDM:	Digital Diagnostic Monitoring functionality as defined in SFF-8472 MSA.