

SO-XFP-ER-CXX

XFP, 10G Multirate, CWDM, DDM, 14dB, 40km, 1470nm-1610nm (8ch)

OVERVIEW

The SO-XFP-ER-Cxx is a versatile CWDM transceiver supporting a wide range of traffic formats. The range performance is in accordance with the IEEE 802.3ae ER/EW-standard, providing a bridgeable distance of up to 40km for 10GbE-LAN (10GBASE-ER) and 10GbE-WAN (10GBASE-EW) services.

The transceiver is available in 8 CWDM wavelengths, spanning from 1470nm to 1610nm in accordance with the G.694.2 standard. This transceiver provides digital diagnostic functions via a 2-wire serial interface as defined by the SFF-8472 specification.

TECHNICAL DATA

Technology	CWDM XFP	
Transmission media	SM (2x LC)	
Typical reach	40 km	
Nominal wavelength	1470 nm - 1610 nm (8ch)	
Interface standards	10GBASE-ER 10GBASE-EW 1200-SM-LL-L 10G FC	
Bit rate range	9.95 - 11.1 Gbps	
Protocols	Eth:	10GbE-LAN 10GbE-WAN
	OTN:	OTU2e OTU2
	SDH/SONET:	STM-64/OC-192
	FC:	10G FC
	CPRI:	Opt 8 (10.1376 Gbps)
Power budget	0 - 14.1 dB	
Dispersion tolerance	800 ps/nm ¹⁾	
Dispersion penalty	2.5 dB ¹⁾	
Temperature range	0°C to +70°C (Cxx)	
Power consumption	< 3.5W	

Transmitter data	Output power:	Min: -0.9 dBm Max: +4.0 dBm
	Tx wavelength:	1470 - 1610 nm in 20nm steps (G.694.2)
Receiver data	Minimum input power:	-15.0 dBm ¹⁾
	Overload (max power):	+0.5 dBm
	Wavelength range:	1260 - 1620 nm
DDM	Yes	
MSA compliance	SFF-8431 SFF-8432 SFF-8472	

¹⁾ @ 10.3Gbps

Regulatory compliance

EMC CE	EN 55022:2010 EN 55024:2010
UL/Safety	UL 60950-1
FCC	47 CFR PART 15 OCT, 2013
RoHS	RoHS 6
TUV	EN 60950-1:2006+A11+A1+A12+A2 EN 60825-1:2014 EN 60825-2:2004+A1+A2

Storage temp.	-40°C to +85°C
----------------------	----------------

Note! See "Definitions" below.

Note: IEEE 802.3ae 10GBASE-ER/EW is defined only at 1550 nm. The standard is referred to from bridgeable distance perspective for the other wavelengths within the CWDM band.

ORDERING INFORMATION

Part number	Description
SO-XFP-ER-C47	XFP, 10G Multirate, CWDM 1470nm, SM, DDM, 14dB, 40km
SO-XFP-ER-C49	XFP, 10G Multirate, CWDM 1490nm, SM, DDM, 14dB, 40km
SO-XFP-ER-C51	XFP, 10G Multirate, CWDM 1510nm, SM, DDM, 14dB, 40km
SO-XFP-ER-C53	XFP, 10G Multirate, CWDM 1530nm, SM, DDM, 14dB, 40km
SO-XFP-ER-C55	XFP, 10G Multirate, CWDM 1550nm, SM, DDM, 14dB, 40km
SO-XFP-ER-C57	XFP, 10G Multirate, CWDM 1570nm, SM, DDM, 14dB, 40km
SO-XFP-ER-C59	XFP, 10G Multirate, CWDM 1590nm, SM, DDM, 14dB, 40km
SO-XFP-ER-C61	XFP, 10G Multirate, CWDM 1610nm, SM, DDM, 14dB, 40km

DEFINITIONS

Technology:	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable. Electrical or optical cable with attached connectors.
Transmission Media:	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach:	Nominal distance performance based on dispersion and power budget properties, i.e. w/o dispersion compensation and optical amplification.
Bit rate range:	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols:	Protocols within supported bit rate range.
Nominal wavelength:	Typical wavelength from transmitter.
Interface standards:	Referenced interface standards e.g. IEEE 802.3 standard for 10GbE services.
Power budget:	Min and max power budget between Transmitter and Receiver. Excluding any dispersion penalty.
Dispersion tolerance/penalty:	Maximum amount of tolerated dispersion and required reduction of power budget to maintain BER better than $1E^{-12}$. Defined at a specific bit rate.
Temperature range:	Max operating case temperature range. Standard temperature range: Typically 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): Typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption:	Worst case power consumption.
Transmitter Output power:	Average output power. Provided in min and max values.
Receiver minimum input power:	Minimum average input power at specified BER, normally $1E^{-12}$.
Receiver max input power:	Maximum average input power at specified BER, normally $1E^{-12}$.
DDM:	Digital Diagnostic Monitoring functionality as defined in SFF-8472 MSA.