

SO-XFP-SR & -SR-E

XFP, 10G Multirate, 850nm, MM, DDM, 3.8dB, 300m@OM3

OVERVIEW

The SO-XFP-SR is an 850nm XFP transceiver for MultiMode fiber supporting traffic formats between 9.95 Gbps to 11.3 Gbps. The optical performance is in accordance with the IEEE 802.3ae SR/SW-standard, providing a bridgeable distance of up to 300m for 10GbE-LAN (10GBASE-SR) and 10GbE-WAN (10GBASE-SW) services. Apart from being ideally suited for 10 GbE datacom applications, it is also well suited for storage area network (SAN/NAS) applications based on 10G Fiber Channel standards.

The transceiver has no minimum distance (i.e. no minimum attenuation) which is ideal for intra-office connections since extra attenuators need not be considered. An OM3 or higher-grade fiber shall be used to avoid distance issues.

This transceiver provides digital diagnostic functions via a 2-wire serial interface as defined by the SFF-8472 specification. The transceiver is available in two temperature range options, one supporting an extended temperature range -20°C to 85°C (-4°F to 185°F).

TECHNICAL DATA

Technology	Grey XFP
Transmission media	MM (2x LC)
Typical reach	300 m @ OM3 fiber
Nominal wavelength	850 nm
Interface standards	10GBASE-SR 10GBASE-SW 1200-M5-SN-I 1200-M5E-SN-I 1200-M6-SN-I
Bit rate range	9.95 - 11.3 Gbps
Protocols	Eth: 10GbE-LAN 10GbE-WAN OTN: OTU2e OTU2 SDH/SONET: STM-64/OC-192 FC: 10G FC CPRI: Opt 8 (10.1376 Gbps)
Power budget	0 - 3.8 dB
Temperature range	0°C to +70°C (SR) -20°C to +85°C (SR-E)
Power consumption	< 1.0W

Transmitter data	Output power:	Min: -7.3 dBm Max: -1.0 dBm
	Tx wavelength:	Min: 840 nm Max: 860 nm
Receiver data	Minimum input power:	-11.1 dBm ¹⁾
	Overload (max power):	-1.0 dBm
	Wavelength range:	840 - 860 nm
DDM		Yes
MSA compliance		SFF-8431 SFF-8472

¹⁾ @ 10.3Gbps

Regulatory compliance

EMC CE	EN 55022:2010 EN 55024:2010
UL/Safety	UL 60950-1
FCC	47 CFR PART 15 OCT, 2013
RoHS	RoHS 6
TUV	EN 60950-1:2006+A11+A1+A12+A2 EN 60825-1:2014 EN 60825-2:2004+A1+A2

Storage temp.	-40°C to +85°C
----------------------	----------------

Note! See "Definitions" below.

ORDERING INFORMATION

Part number	Description
SO-XFP-SR	XFP, 10G Multirate, 850nm, MM, DDM, 3.8dB, 300m@OM3
SO-XFP-SR-E	XFP, 10G Multirate, 850nm, MM, DDM, 3.8dB, 300m@OM3, E-temp

DEFINITIONS

Technology:	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable. Electrical or optical cable with attached connectors.
Transmission Media:	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach:	Nominal distance performance based on dispersion and power budget properties, i.e. w/o dispersion compensation and optical amplification.
Bit rate range:	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols:	Protocols within supported bit rate range.
Nominal wavelength:	Typical wavelength from transmitter.
Interface standards:	Referenced interface standards e.g. IEEE 802.3 standard for 10GbE services.
Power budget:	Min and max power budget between Transmitter and Receiver. Excluding any dispersion penalty.
Dispersion tolerance/penalty:	Maximum amount of tolerated dispersion and required reduction of power budget to maintain BER better than $1E^{-12}$. Defined at a specific bit rate.
Temperature range:	Max operating case temperature range. Standard temperature range: Typically 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): Typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption:	Worst case power consumption.
Transmitter Output power:	Average output power. Provided in min and max values.
Receiver minimum input power:	Minimum average input power at specified BER, normally $1E^{-12}$.
Receiver max input power:	Maximum average input power at specified BER, normally $1E^{-12}$.
DDM:	Digital Diagnostic Monitoring functionality as defined in SFF-8472 MSA.