

SO-QSFP28-PSM4

QSFP28, 100GBase, 1310nm, SM, DDM, 4.7dB, 2km, MPO

OVERVIEW


The SO-QSFP28-PSM4 is a QSFP28 form-factor transceiver for 100 Gbps Ethernet applications. It is intended for use in inter- and intra-connect applications within and between data centers between switches, routers, storage equipment etc. The optical performance is based on the 100GBASE PSM4 MSA industry standard where the minimum required operating range is up to 500m over a SingleMode (SM) 8-fiber ribbon cable.

SO-QSFP28-PSM4 has an optical performance enabling distances of up to 2km over a SingleMode (SM) ribbon fiber. Forward Error Correction (FEC) is required to be implemented by the host in order to ensure reliable system operation. The FEC type shall be as defined in IEEE802.3bj, i.e. Reed Solomon RS(528,514). The optical parameters will provide a bit error ratio (BER) of 5×10^{-5} . FEC will render in the required BER of better than 1×10^{-12} .

SO-QSFP28-PSM4 uses four 1310nm channels/lanes @ 25.78 Gbps to transport the Ethernet signal. The transceiver has a single 12 lane optical fiber MPO/MTP-connector interface. Digital diagnostics functions (DDM) are available via an I2C interface, as specified by the QSFP28 MSA.

TECHNICAL DATA

| | | |
|----------------------------|---|--------------------------------|
| Technology | Grey QSFP28 | |
| Transmission media | SM (1x MPO) | |
| Typical reach | 2 km | |
| Nominal wavelength | 4x 1310 nm | |
| Interface standards | 100GBASE-PSM4 | |
| Bit rate range | 103.12 Gbps ¹⁾ 25.78 Gbps ²⁾ | |
| Protocols | Eth: | 100GbE |
| Power budget | | 0 – 4.7 dB |
| Temperature range | | 0°C to +70°C |
| Power consumption | | < 3.5 W |
| Transmitter data | Output power, tot: | Max: +8.0 dBm ³⁾ |
| | Output power, per lane | Min: -5.5 dBm Max: +2.0 dBm |
| | Tx wavelength (nm): | 1295 – 1325 |
| Receiver data | Minimum input power: | -10.2 dBm ⁵⁾ |
| | Overload (max power): | +2.0 dBm ⁵⁾ |
| | Wavelength range: | 1295 – 1325 ⁵⁾ |
| DDM | | Yes |
| MSA compliance | | QSFP28 MSA PSM4 MSA |



MPO/MTP connector

- ¹⁾ Aggregated line rate 100GbE
- ²⁾ Line rate per lane
- ³⁾ The combined average launch power from all four lanes
- ⁴⁾ Line rate per lane
- ⁵⁾ Per lane (25.78 Gbps)

| | |
|------------------|---|
| EMC CE | EN 55032:2012, EN 55032:2015 EN 55024:2010, EN 55024:2010+A1 |
| UL/Safety | UL 60950-1 |
| FCC | 47 CFR PART 15 OCT, 2013 |
| RoHS | RoHS 6 |
| TUV | EN 60950-1:2006+A11+A1+A12+A2 EN 60825-1:2014 EN 60825-2:2004+A1+A2 |

| | |
|----------------------|----------------|
| Storage temp. | -40°C to +85°C |
|----------------------|----------------|

Note! See “Definitions” below.

MPO (Multi-fiber Push On) is an optical connector for ribbon cables with four to twenty-four fibers. MTP is a specific brand of an MPO connector.

ORDERING INFORMATION

| Part number | Description |
|----------------|--|
| SO-QSFP28-PSM4 | QSFP28, 100GBase, 1310nm, SM, DDM, 4.7dB, 2km, MPO |

DEFINITIONS

| | |
|-------------------------------|---|
| Technology: | Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable (DAC). Electrical or optical cable with attached connectors. |
| Transmission Media: | Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO). |
| Typical reach: | Nominal distance performance based on dispersion and power budget properties, i.e. w/o dispersion compensation and optical amplification. |
| Bit rate range: | Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps). |
| Protocols: | Protocols within supported bit rate range. |
| Nominal wavelength: | Typical wavelength from transmitter. |
| Interface standards: | Referenced interface standards e.g. IEEE 802.3 standard for 10GbE services. |
| Power budget: | Min and max power budget between Transmitter and Receiver. Excluding any dispersion penalty. |
| Dispersion tolerance/penalty: | Maximum amount of tolerated dispersion and required reduction of power budget to maintain BER better than $1E^{-12}$. Defined at a specific bit rate. |
| Temperature range: | Max operating case temperature range. Standard temperature range: typically 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F) |
| Power consumption: | Worst case power consumption. |
| Transmitter Output power: | Average output power. Provided in min and max values. |
| Receiver minimum input power: | Minimum average input power at specified BER, normally $1E^{-12}$. |
| Receiver max input power: | Maximum average input power giving a BER, normally $1E^{-12}$. |
| DDM: | Digital Diagnostic Monitoring functionality as defined in SFF-8472 MSA. |