

# SO-CFP4-SR4

CFP4, 100GBASE-SR4, 1310nm, MM, DDM, 100m, MPO (MTP12)

## OVERVIEW

The SO-CFP4-SR4 is a CFP4 form-factor transceiver for 100 Gbps Ethernet (100GBASE-SR4) applications. It is intended for use in inter- and intra-connect applications within data centers between switches, routers, storage equipment etc. The optical performance is in accordance with the 100GBASE-SR standard, i.e. for optical distances up to 100m over a MultiMode (MM) OM4-grade ribbon fiber.

SO-CFP4-SR4 uses 4x channels @ 25.78 Gbps to transport an 100G Ethernet signal. The transceiver has a single 12 lane optical fiber MPO/MPT-connector interface.


## TECHNICAL DATA

<b>Technology</b>	Grey CFP4
<b>Transmission media</b>	MM (1x MPO)
<b>Typical reach</b>	70 m @ OM3 100 m @ OM4
<b>Nominal wavelength</b>	850 nm
<b>Interface standards</b>	100GBASE-SR4
<b>Bit rate range</b>	103.125 Gbps <sup>1)</sup> 25.78 Gbps <sup>2)</sup>
<b>Protocols</b> Eth:	100GbE
<b>Power budget</b>	0 - 1.9 dB
<b>Temperature range</b>	0°C to +70°C
<b>Power consumption</b>	< 4 W

<sup>1)</sup> Aggregated line rate (100GbE)

<sup>2)</sup> Per channel line rate

<sup>3)</sup> Per channel/lane



MPO/MPT connector

<b>Transmitter data</b>	<b>Output power, per lane</b>	Min: -8.4 dBm <sup>3)</sup> Max: +2.4dBm <sup>3)</sup>
	<b>Wavelength range:</b>	840 – 860 nm <sup>3)</sup>
<b>Receiver data</b>	<b>Minimum input power:</b>	-10.3 dBm <sup>3)</sup>
	<b>Overload (max power):</b>	+2.4 dBm <sup>3)</sup>
	<b>Wavelength range:</b>	840 – 860 nm <sup>3)</sup>
<b>DDM</b>		Yes
<b>MSA compliance</b>		CFP4 MSA

### Regulatory compliance

<b>EMC CE</b>	EN 55022:2010 EN 55024:2010
<b>UL/Safety</b>	UL 60950-1
<b>RoHS</b>	RoHS 6
<b>TUV</b>	EN 60825-1: 2007 EN 60825-2:2004+A1+A2

<b>Storage temp.</b>	-40°C to +85°C
----------------------	----------------

**Note! See “Definitions” below.**

MPO (Multi-fiber Push On) is an optical connector for ribbon cables with four to twenty-four fibers. MPT is a specific brand of an MPO connector.

Note: IEEE 802.3bx stipulates that 100GBASE-SR4 interfaces requires FEC. Host equipment normally enable FEC automatically when using SR4 type transceivers. Receiver sensitivity values are given at BER  $5 \times 10^{-5}$ , i.e. prior FEC. BER will be better than  $10^{-12}$  when FEC is applied.

## ORDERING INFORMATION

Part number	Description
SO-CFP4-SR4	CFP4, 100GBASE-SR4, 1310nm, MM, DDM, 100m, MPO (MTP12)

## DEFINITIONS

Technology:	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable (DAC). Electrical or optical cable with attached connectors.
Transmission Media:	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach:	Nominal distance performance based on dispersion and power budget properties, i.e. w/o dispersion compensation and optical amplification.
Bit rate range:	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols:	Protocols within supported bit rate range.
Nominal wavelength:	Typical wavelength from transmitter.
Interface standards:	Referenced interface standards e.g. IEEE 802.3 standard for 10GbE services.
Power budget:	Min and max power budget between Transmitter and Receiver. Excluding any dispersion penalty.
Dispersion tolerance/penalty:	Maximum amount of tolerated dispersion and required reduction of power budget to maintain BER better than $1E^{-12}$ . Defined at a specific bit rate.
Temperature range:	Max operating case temperature range. Standard temperature range: typically 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption:	Worst case power consumption.
Transmitter Output power:	Average output power. Provided in min and max values.
Receiver minimum input power:	Minimum average input power at specified BER, normally $1E^{-12}$ .
Receiver max input power:	Maximum average input power giving a BER, normally $1E^{-12}$ .
DDM:	Digital Diagnostic Monitoring functionality as defined in SFF-8472 MSA.