

SO-SFP-100BASE-BX40D-35 & -53

SFP, BiDi, 100/155Mbps, 1310/1550nm, SM, DDM, 28dB, 40km

OVERVIEW


The SO-SFP-100BASE-BX40D is a bi-directional transceiver solution operating directly on a single-fiber without the need for a separate optical filter. This is achieved by having two transceivers that inject different wavelengths into the same single-fiber. The solution thus consists of two transceivers; SO-SFP-100Base-BX40D-35 and SO-SFP-100Base-BX40D-53, operating at 1310nm and 1550nm respectively. Using a single-fiber solution provides a cost-efficient solution for interconnect and it simplifies the patching since no separate transmit/receive direction has to be taken into account.

The transceiver pair supports the bit rate range from 100Mbps to 155Mbps, i.e. Fast Ethernet (FE) and STM-1/OC-3 services. The optical performance of the transceiver pair provides a bridgeable distance of up to 40km.

The transceivers provide digital diagnostic functions via a 2-wire serial interface as defined by the SFF-8472 specification.

TECHNICAL DATA

Technology	BiDi SFP	
Transmission media	SM (1x LC)	
Typical reach	40 km	
Nominal wavelength	1310 nm ¹⁾ & 1550 nm ²⁾	
Bit rate range	100 – 155.52 Mbps	
Protocols	Eth:	FE
	SDH/SONET:	STM-1/OC-3
Power budget	0.0 - 28.0 dB ³⁾	
Temperature range	0°C to +70°C	
Power consumption	< 1.0W	



Transmitter data	Output power:	Min: -5.0 dBm Max: 0.0 dBm
	Tx wavelength:	1260 - 1360 nm ¹⁾ 1500 - 1580 nm ²⁾
Receiver data	Minimum input power:	-34.0 dBm ³⁾
	Overload (max power):	0.0 dBm
	Wavelength range:	1500 - 1580 nm ¹⁾ 1260 - 1360 nm ²⁾
DDM	Yes	
MSA compliance	SFP MSA SFF 8472	

¹⁾ SO-SFP-100Base-BX40D-35

²⁾ SO-SFP-100Base-BX40D-53

³⁾ STM-1/OC-3

Regulatory compliance

EMC CE	EN 55022:2010 EN 55024:2010
UL/Safety	UL 60950-1
FCC	47 CFR PART 15 OCT, 2013
RoHS	RoHS 6
TUV	EN 60950-1:2006+A11+A1+A12+A2 EN 60825-1:2014 EN 60825-2:2004+A1+A2

Storage temp.	-40°C to +85°C
----------------------	----------------

Note! See “Definitions” below.

ORDERING INFORMATION

Part number	Description
SO-SFP-100Base-BX40D-35	SFP BiDi, 100Base, TX/RX=1310/1550nm, SM, DDM, 28dB, 40km
SO-SFP-100Base-BX40D-53	SFP BiDi, 100Base, TX/RX=1550/1310nm, SM, DDM, 28dB, 40km

DEFINITIONS

Technology:	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable. Electrical or optical cable with attached connectors.
Transmission Media:	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach:	Nominal distance performance based on dispersion and power budget properties, i.e. w/o dispersion compensation and optical amplification.
Bit rate range:	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols:	Protocols within supported bit rate range.
Nominal wavelength:	Typical wavelength from transmitter.
Interface standards:	Referenced interface standards e.g. IEEE 802.3 standard for 10GbE services.
Power budget:	Min and max power budget between Transmitter and Receiver. Excluding any dispersion penalty.
Dispersion tolerance/penalty:	Maximum amount of tolerated dispersion and required reduction of power budget to maintain BER better than $1E^{-12}$. Defined at a specific bit rate.
Temperature range:	Max operating case temperature range. Standard temperature range: Typically 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): Typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption:	Worst case power consumption.
Transmitter Output power:	Average output power. Provided in min and max values.
Receiver minimum input power:	Minimum average input power at specified BER, normally $1E^{-12}$.
Receiver max input power:	Maximum average input power at specified BER, normally $1E^{-12}$.
DDM:	Digital Diagnostic Monitoring functionality as defined in SFF-8472 MSA.