



DS-32G-IR-Dxxxx

SFP28, 32/16/8G FC, DWDM 100GHz grid, 192.00 - 196.00THz (41ch), 10km, 7dB, LC, D2955-D6142

OVERVIEW

The DS-32G-IR-Dxxxx is a versatile DWDM transceiver in SFP28 form-factor supporting a wide range of Fiber Channel (FC) services (8G to 32G). The transceiver is provided in versions covering all C-band channels in the 100GHz DWDM grid as specified in the ITU-T G.694.1 standard. The transceiver has been layer-1 tested and approved by Cisco.

The transceiver has an inbuilt 3-mode CDR (Clock Data Recovery) function;

- High data rate mode for 32G FC
- Low data rate mode for 16G FC
- Bypass mode for 8 GFC

The optical performance provides a bridgeable distance of up to 10km (without dispersion compensation) for 32G FC. This transceiver provides digital diagnostic functions via a 2-wire serial interface as defined by the SFF-8472 specification.

The transceiver module is compliant to RoHS-6/6.

TECHNICAL DATA

Technology	DWDM 100GHz SFP28
Transmission media	SM (2x LC)
Typical reach	10 km
Nominal wavelength	191.50 - 196.10 THz
Bit rate range	28.05 Gbps
	14.025 Gbps
	8.500 Gbps
Protocols	FC:
	32G
	16G
	8G
Power budget	0 - 7.0 dB
Dispersion tolerance	-170 to +170 ps/nm ¹⁾
Temperature range	0°C to +70°C
Power consumption	< 2.0W

Transmitter data	Output power (avg):	Min: -3.0 dBm ¹⁾ Max: +2.0 dBm ¹⁾
	Tx wavelength:	192.15 - 196.10 THz in 100GHz steps ITU-T G.694.1
Receiver data	Minimum input power:	-10.0 dBm ¹⁾²⁾
	Max input power:	+2.0 dBm
	Wavelength range:	1480 – 1580 nm
DDM		Yes
MSA compliance		SFP28 SFF-8402

¹⁾ @ 28.05 Gbps (32G FC)

²⁾ @ BER < 1E-6 using PRBS 2³¹-1



Regulatory compliance

EMC CE	EN 55022:2010 EN 55024:2010
UL/Safety	UL 60950-1
FCC	47 CFR PART 15 OCT, 2013
RoHS	RoHS 6
TUV	EN 60950-1:2006+A11+A1+A12+A2
	EN 60825-1:2014
	EN 60825-2:2004+A1+A2

Storage temp.	-40°C to 85°C
---------------	---------------

Note: Optical BER performance is specified at a BER 1E-6 implying that Reed Solomon RS-FEC encoding/decoding shall be used to provide sufficient BER performance.

ORDERING INFORMATION

Part number	Freq. THz	λ nm
DS-32G-IR-D6142	192.00	1561.42
DS-32G-IR-D6061	192.10	1560.61
DS-32G-IR-D5979	192.20	1559.79
DS-32G-IR-D5898	192.30	1558.98
DS-32G-IR-D5817	192.40	1558.17
DS-32G-IR-D5736	192.50	1557.36
DS-32G-IR-D5655	192.60	1556.55
DS-32G-IR-D5575	192.70	1555.75
DS-32G-IR-D5494	192.80	1554.94
DS-32G-IR-D5413	192.90	1554.13
DS-32G-IR-D5333	193.00	1553.33
DS-32G-IR-D5252	193.10	1552.52
DS-32G-IR-D5172	193.20	1551.72
DS-32G-IR-D5092	193.30	1550.92
DS-32G-IR-D5012	193.40	1550.12
DS-32G-IR-D4932	193.50	1549.32
DS-32G-IR-D4851	193.60	1548.51
DS-32G-IR-D4772	193.70	1547.72
DS-32G-IR-D4692	193.80	1546.92
DS-32G-IR-D4612	193.90	1546.12
DS-32G-IR-D4532	194.00	1545.32

Part number	Freq. THz	λ nm
DS-32G-IR-D4453	194.10	1544.53
DS-32G-IR-D4373	194.20	1543.73
DS-32G-IR-D4294	194.30	1542.94
DS-32G-IR-D4214	194.40	1542.14
DS-32G-IR-D4135	194.50	1541.35
DS-32G-IR-D4056	194.60	1540.56
DS-32G-IR-D3977	194.70	1539.77
DS-32G-IR-D3898	194.80	1538.98
DS-32G-IR-D3819	194.90	1538.19
DS-32G-IR-D3740	195.00	1537.40
DS-32G-IR-D3661	195.10	1536.61
DS-32G-IR-D3582	195.20	1535.82
DS-32G-IR-D3504	195.30	1535.04
DS-32G-IR-D3425	195.40	1534.25
DS-32G-IR-D3347	195.50	1533.47
DS-32G-IR-D3268	195.60	1532.68
DS-32G-IR-D3190	195.70	1531.90
DS-32G-IR-D3112	195.80	1531.12
DS-32G-IR-D3033	195.90	1530.33
DS-32G-IR-D2955	196.00	1529.55

DEFINITIONS

Technology:	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable. Electrical or optical cable with attached connectors.
Transmission Media:	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach:	Nominal distance performance based on dispersion and power budget properties, i.e. w/o dispersion compensation and optical amplification.
Bit rate range:	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols:	Protocols within supported bit rate range.
Nominal wavelength:	Typical wavelength from transmitter.
Interface standards:	Referenced interface standards e.g. IEEE 802.3 standard for 10GbE services.
Power budget:	Min and max power budget between Transmitter and Receiver. Excluding any dispersion penalty.
Dispersion tolerance/penalty:	Maximum amount of tolerated dispersion and required reduction of power budget to maintain BER better than $1E^{-12}$. Defined at a specific bit rate.
Temperature range:	Max operating case temperature range. Standard temperature range: Typically 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): Typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption:	Worst case power consumption.
Transmitter Output power:	Average output power. Provided in min and max values.
Receiver minimum input power:	Minimum average input power at specified BER, normally $1E^{-12}$.
Receiver max input power:	Maximum average input power at specified BER, normally $1E^{-12}$.
DDM:	Digital Diagnostic Monitoring functionality as defined in SFF-8472 MSA.